

## NAME

Net::Time - time and daytime network client interface

## SYNOPSIS

```
use Net::Time qw(inet_time inet_daytime);

print inet_time();           # use default host from Net::Config
print inet_time('localhost');
print inet_time('localhost', 'tcp');

print inet_daytime();        # use default host from Net::Config
print inet_daytime('localhost');
print inet_daytime('localhost', 'tcp');
```

## DESCRIPTION

Net::Time provides subroutines that obtain the time on a remote machine.

`inet_time ( [HOST [, PROTOCOL [, TIMEOUT]]])`

Obtain the time on `HOST`, or some default host if `HOST` is not given or not defined, using the protocol as defined in RFC868. The optional argument `PROTOCOL` should define the protocol to use, either `tcp` or `udp`. The result will be a time value in the same units as returned by `time()` or `undef` upon failure.

`inet_daytime ( [HOST [, PROTOCOL [, TIMEOUT]]])`

Obtain the time on `HOST`, or some default host if `HOST` is not given or not defined, using the protocol as defined in RFC867. The optional argument `PROTOCOL` should define the protocol to use, either `tcp` or `udp`. The result will be an ASCII string or `undef` upon failure.

## AUTHOR

Graham Barr <[gbarr@pobox.com](mailto:gbarr@pobox.com)>

Steve Hay <[shay@cpan.org](mailto:shay@cpan.org)> is now maintaining libnet as of version 1.22\_02

## COPYRIGHT

Versions up to 2.11 Copyright (c) 1995-2004 Graham Barr. All rights reserved. Changes in Version 2.11 onwards Copyright (C) 2014 Steve Hay. All rights reserved.

This program is free software; you can redistribute it and/or modify it under the same terms as Perl itself.