

## NAME

Pod::Perldoc::GetOptsOO - Customized option parser for Pod::Perldoc

## SYNOPSIS

```
use Pod::Perldoc::GetOptsOO ();

Pod::Perldoc::GetOptsOO::getopts( $obj, \@args, $truth )
    or die "wrong usage";
```

## DESCRIPTION

Implements a customized option parser used for *Pod::Perldoc*.

Rather like Getopt::Std's getopts:

Call Pod::Perldoc::GetOptsOO::getopts(\$object, \@ARGV, \$truth)

Given -n, if there's a opt\_n\_with, it'll call \$object->opt\_n\_with( ARGUMENT ) (e.g., "-n foo" => \$object->opt\_n\_with('foo'). Ditto "-nfoo")

Otherwise (given -n) if there's an opt\_n, we'll call it \$object->opt\_n(\$truth) (Truth defaults to 1)

Otherwise we try calling \$object->handle\_unknown\_option('n') (and we increment the error count by the return value of it)

If there's no handle\_unknown\_option, then we just warn, and then increment the error counter

The return value of Pod::Perldoc::GetOptsOO::getopts is true if no errors, otherwise it's false.

## SEE ALSO

*Pod::Perldoc*

## COPYRIGHT AND DISCLAIMERS

Copyright (c) 2002-2007 Sean M. Burke.

This library is free software; you can redistribute it and/or modify it under the same terms as Perl itself.

This program is distributed in the hope that it will be useful, but without any warranty; without even the implied warranty of merchantability or fitness for a particular purpose.

## AUTHOR

Current maintainer: Mark Allen <mallen@cpan.org>

Past contributions from: brian d foy <bdfey@cpan.org> Adriano R. Ferreira <ferreira@cpan.org>, Sean M. Burke <sburke@cpan.org>