

NAME

Pod::Simple::RTF -- format Pod as RTF

SYNOPSIS

```
perl -MPod::Simple::RTF -e \
    "exit Pod::Simple::RTF->filter(shift)->any_errata_seen" \
    thingy.pod > thingy.rtf
```

DESCRIPTION

This class is a formatter that takes Pod and renders it as RTF, good for viewing/printing in MSWord, WordPad/write.exe, TextEdit, etc.

This is a subclass of *Pod::Simple* and inherits all its methods.

FORMAT CONTROL ATTRIBUTES

You can set these attributes on the parser object before you call `parse_file` (or a similar method) on it:

```
$parser->head1_halfpoint_size( halfpoint_integer );
```

```
$parser->head2_halfpoint_size( halfpoint_integer );
```

```
$parser->head3_halfpoint_size( halfpoint_integer );
```

```
$parser->head4_halfpoint_size( halfpoint_integer );
```

These methods set the size (in half-points, like 52 for 26-point) that these heading levels will appear as.

```
$parser->codeblock_halfpoint_size( halfpoint_integer );
```

This method sets the size (in half-points, like 21 for 10.5-point) that codeblocks ("verbatim sections") will appear as.

```
$parser->header_halfpoint_size( halfpoint_integer );
```

This method sets the size (in half-points, like 15 for 7.5-point) that the header on each page will appear in. The header is usually just "*modulename* p. *pagenumber*".

```
$parser->normal_halfpoint_size( halfpoint_integer );
```

This method sets the size (in half-points, like 26 for 13-point) that normal paragraphic text will appear in.

```
$parser->no_proofing_exemptions( true_or_false );
```

Set this value to true if you don't want the formatter to try putting a hidden code on all Perl symbols (as best as it can notice them) that labels them as being not in English, and so not worth spellchecking.

```
$parser->doc_lang( microsoft_decimal_language_code )
```

This sets the language code to tag this document as being in. By default, it is currently the value of the environment variable `RTFDEFLANG`, or if that's not set, then the value 1033 (for US English).

Setting this appropriately is useful if you want to use the RTF to spellcheck, and/or if you want it to hyphenate right.

Here are some notable values:

1033	US English
2057	UK English
3081	Australia English
4105	Canada English

```
1034 Spain Spanish
2058 Mexico Spanish
1031 Germany German
1036 France French
3084 Canada French
1035 Finnish
1044 Norwegian (Bokmal)
2068 Norwegian (Nynorsk)
```

If you are particularly interested in customizing this module's output even more, see the source and/or write to me.

SEE ALSO

Pod::Simple, *RTF::Writer*, *RTF::Cookbook*, *RTF::Document*, *RTF::Generator*

SUPPORT

Questions or discussion about POD and Pod::Simple should be sent to the pod-people@perl.org mail list. Send an empty email to pod-people-subscribe@perl.org to subscribe.

This module is managed in an open GitHub repository, <https://github.com/theory/pod-simple/>. Feel free to fork and contribute, or to clone [git://github.com/theory/pod-simple.git](https://github.com/theory/pod-simple.git) and send patches!

Patches against Pod::Simple are welcome. Please send bug reports to [<bug-pod-simple@rt.cpan.org>](mailto:bug-pod-simple@rt.cpan.org).

COPYRIGHT AND DISCLAIMERS

Copyright (c) 2002 Sean M. Burke.

This library is free software; you can redistribute it and/or modify it under the same terms as Perl itself.

This program is distributed in the hope that it will be useful, but without any warranty; without even the implied warranty of merchantability or fitness for a particular purpose.

AUTHOR

Pod::Simple was created by Sean M. Burke [<sburke@cpan.org>](mailto:sburke@cpan.org). But don't bother him, he's retired.

Pod::Simple is maintained by:

* Allison Randal allison@perl.org

* Hans Dieter Pearcey hdp@cpan.org

* David E. Wheeler dwheeler@cpan.org